

## Installation Procedure

### 9000-Pro OS Factory Setup Data Disk

**To start:** This operation will reset the data to the factory setup and erase the previous data. Before you start, we recommend making a backup of the personal data in your instrument. It requires two floppy disks to save everything. See "Backing Up/Restoring the Data in Flash ROM" on the owner's manual page 154 for the instruction.

1. After you extract the components of the zip file, double click the "SetupPro.exe" file.
2. The following files will automatically be saved in the same folder where "SetupPro.exe" is located:

Folder Name	Contents
Disk1	Disk.mng, BACKUP.b01 (folder)
Disk2	Disk.mng, BACKUP.b02 (folder)

3. Prepare two formatted floppy disks. Write down the name to the labels and put them to each disk.
4. Copy the contents of each folder to the root directory of the floppy disk. This means you need to copy both Disk.mng and BACKUP.b01 folder to the floppy disk "Disk1" and copy Disk.mng and BACKUP.b02 folder to the floppy disk "Disk2".
5. Take the floppy disks to your instrument.
6. Press [DISK/SCSI] button and go to DISK MENU.
7. Press [BACKUP/RESTORE] on the LCD button [D] and then press [RESTORE] on the LCD button [B].
8. Insert the "Disk1" and you will see the folder name "BACKUP.b01" at the FILE column.

9. Press [NEXT] once, then the following screen will appear:



10. You can choose which data is restored and reset to the factory data. For example, if you want to restore the factory data of One Touch Setting, turn off all switches except OTS.
11. After you select the desired data, press [NEXT]. Then follow the screen message and proceed with the loading.
12. When the loading is finished, "Completed" message will appear. Press [EXIT] several times and return to the main screen.